



TRYNOX®

CLAMPSENSE™



Trynox Clampsense™ is intended to mitigate the possibility of cracking or gasket debris. Fits to sanitary stainless steel tubing, surface finishing 150 Grit OD. Has a maximum operating pressure rating of 140 psi at 70 degrees F ambient temperature.

FITTINGS



TRYNOX Sanitary fittings are in use around the world in dairies, distilleries, breweries, food processing plants and cosmetics—wherever product purity is important. These fittings are also utilized in process tubing systems where COP is not required or where CIP can be accomplished.

OUR PRODUCTS



VALVES


Trynox Sanitary valves has an ultra slim or sphere design, a variety of sanitary valves available following either 3A or ASME BPE standards, Piston, Butterfly, Relief, Ball, Diaphragm, Plug and sample cooks.


We have some of the best stainless steel tubing on the market. All of our sanitary tubing meets 3A standards and come in a variety of sizes. We can set you up with a complete set of tubing for your needs including pipe hangers, stainless steel tubing and filters and strainers.



TUBING

 www.chemsealinc.net

 +1 (888) 337.0649

 sales@chemsealinc.net

If you want to know more information about our product, you can contact us via email or you can give us a call.

TRYNOX® DISTRIBUTED BY CHEMSEAL® INC