

# V1000-4X

1/8 to 25 HP

NEMA 4X Current Vector Microdrive



## Washdown - Dust Tight!

The V1000-4X is a version of the standard V1000 in an integral enclosure that meets NEMA type 4X/12 *indoor use requirements*, UL type 4X/12 standards, and the IP66 rating of IEC 60529. This enclosure provides the protection required in tough washdown or dust-tight environments, common in Food and Beverage Processing, Packaging, Metal Machining, Woodworking, Pumping, Refrigeration, and Printing. The enclosure is epoxy-coated to protect against the harmful effects of sanitizing chemicals commonly used in food industries.

## Features

- NEMA Type 4X/IP66 enclosure
- Corrosion-resistant
- Current vector control, open loop
- RoHS compliance
- On-line tuning
- Induction motor (IM) or permanent magnet synchronous motor (PM) operation
- Function Block Diagram (FBD) programming via DriveWorksEZ™
- Starting torque of 200% at 0.5 Hz
- Removable terminal block with parameter backup function
- "One-touch" copy function with verify
- Super-fast 2 ms scan cycle with dual CPU
- EN954-1 Safety Cat. 3, Stop Cat. 0
- Increased vibration resistance, from 20 Hz to 50 Hz (0.65G)
- 1 in 10,000 failure rate
- Swing PWM function to decrease noise at low carrier frequencies
- Pre-maintenance function
- Modbus communication
- MTBF: 28 years
- Short Circuit Current Rating (SCCR): 30kA rms symmetrical
- Common programming with all other Yaskawa drives

# YASKAWA

**IT'S PERSONAL  
YASKAWA**

YASKAWA AMERICA, INC.  
DRIVES & MOTION DIVISION  
1-800-YASKAWA      YASKAWA.COM

Follow us:



©2017 Yaskawa America Inc.